


# CERTIFICATE

<b>Certificate holder</b>	<b>Rockwool Finland Oy</b> <b>Pakkalankuja 6, P.O. Box 78</b> <b>FI-01511 Vantaa, Finland</b>
<b>Production site</b>	Rockwool-North LLC Industrial Zone, Lazarevka RU-188800 Vyborg, Russia
<b>Products</b>	Thermal insulation products for buildings as specified in Annex 1.
<b>Testing basis</b>	Product standard EN 13162:2012+A1:2015 Insulation KEYMARK Scheme for Thermal Insulation Products, version 2.1.
<b>Mark of conformity</b>	
<b>Registration No.</b>	017
<b>Valid until</b>	30.03.2023
<b>Right of use</b>	This certificate entitles the holder to use the mark of conformity shown above in conjunction with the specified registration number.

Tiina Ala-Outinen  
Manager, Structures

Tiina Tirkkonen  
Senior Expert

ANNEXES: Annex 1: Certified products

**Certified products**

Product	Description	Thickness, mm	Thermal conductivity $\lambda_D$ , W/mK	Reaction to fire	Designation code
A-Batts	Unfaced slab	30 - 250	0,036	A1	MW-EN13162-T3-DS(70,90)-WS-MU1
Facade 1	Unfaced slab	50 - 200	0,034	A1	MW-EN13162-T3-DS(70,90)-CS(10)5-WS-MU1
Façade Batts	Unfaced slab	50 - 250	0,038	A1	MW-EN13162-T4-DS(70,90)-CS(10)20-TR10-WS-MU1
FLEXIBATTS	Unfaced slab	95 - 250	0,036	A1	MW-EN13162-T2-DS(70,90)-WS-MU1
FLEXIBATTS	Unfaced slab	30 - 94	0,036	A1	MW-EN13162-T3-DS(70,90)-WS-MU1
Hardrock 37	Fleece faced slab with or without grooves	50 - 200	0,037	A2-s1, d0	MW-EN13162-T4-DS(70,90)-CS(10)30-PL(5)400-WS-MU1
Slab 150	Unfaced slab	50 - 120	0,038	A1	MW-EN13162-T4-DS(70,90)-CS(10)50-WS-MU1
Slab 150	Fleece faced slab	30 - 40	0,038	A2-s1, d0	MW-EN13162-T4-DS(70,90)-CS(10)50-PL(5)500-WS-MU1
Super A-Batts	Unfaced slab	30 - 250	0,034	A1	MW-EN13162-T3-DS(70,90)-WS-MU1
Spanrock XS	Unfaced slab	80 - 180	0,036	A1	MW-EN13162-T5
Spanrock M	Unfaced slab	100 - 150	0,036	A1	MW-EN13162-T5
Spanrock L	Unfaced slab	100 - 150	0,038	A1	MW-EN13162-T5
TF Board	Unfaced or fleece faced slab with or without grooves	30 - 50	0,039	A2-s1, d0	MW-EN13162-T4-DS(70,90)-CS(10)80-PL(5)700-WS-MU1
TOPROCK Lamella 30	Unfaced lamella	380	0,038	A2-s1, d0	MW-EN13162-T4-DS(70,90)-CS(10)30-WS-MU1
TOPROCK Lamella 50	Unfaced lamella	240 - 450	0,040	A2-s1, d0	MW-EN13161-T4-DS(70,90)-CS(Y)50-WS-MU1
Underlay roof slab 60	Unfaced slab	50 - 130	0,038	A1	MW-EN13162-T3-DS(70,90)-CS(10)60-PL(5)500-WS-MU1
URS 36	Unfaced slab with or without grooves	50 - 200	0,036	A2-s1, d0	MW-EN13162-T4-DS(70,90)-CS(10)30-PL(5)250-WS-MU1
WPI PLUS	Fleece faced slab	30 - 120	0,033	A2-s1, d0	MW-EN13162-T4-WS-MU1