

NBS Specification: FIREPRO® Intumescent Pillow CE

PRODUCT SUMMARY:

Temporary firestop solution for service voids in walls.

PRODUCT GENERAL DESCRIPTION:

ROCKWOOL Intumescent Pillows CE provide up to two hours (El 120) fire protection for differing services. They are designed to provide fire stopping to metal services, plastic conduits and cables passing through fire resisting compartment walls.

The product consists of intumescent material encased within a waterproof glass cloth bag, designed to create a temporary or permanent fire seal around all types of services to maintain continuity of fire performance of compartment walls. They are an ideal solution for applications where services are required to be changed or replaced on a regular basis. Easy to install, they are simply packed tightly in between penetrating services and the wall.

FEATURES AND BENEFITS:

- Easy to install
- Easy to remove and reinstate when changing services
- Maintenance free
- Dry system

APPLICATION:

Under fire conditions, Intumescent Pillows CE expand several times their original volume to form an effective seal around service penetrations. Intumescent Pillows CE are suitable for use with:

- Metal pipework
- Plastic conduits
- Cable trays/ ladders

Note: For applications inside metal cable trunkings please contact ROCKWOOL.

PRODUCT SPECIFICATION CLAUSE

PRODUCT REFERENCE:

FIREPRO® Intumescent Pillow CE

PRODUCT PROPERTIES:

Acoustical Performance: Rw (C,Ctr) = 33 (0,-2)

Air permeability: Tested to EN 1026

General requirements: Insulation products generally

Size:

• 330 x 50 x 20 mm - As required to fill small voids.

330 x 200 x 25 mm - 180 per m² opening.

330 x 200 x 45 mm - 113 per m² opening.

Fire performance: Up to EI 120 fire resistance.

CONTACT DETAILS:

ROCKWOOL

Wern Tarw Road, Rhiwceiliog Pencoed, Bridgend CF35 6NY

Email: technical.solutions@rockwool.co.uk

Telephone: 01656 868 490 www.rockwool.com/uk/